

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

Having described the invention the following is claimed:

1. A steering wheel comprising a rim portion, a spoke portion, and a foamed padding material adhered to at least one of said rim portion and said spoke portion, said foamed padding material including a first portion and a second portion, said first portion having cellular structure and a substantially uniform cell density, said second portion having a continuous external surface free of interruption by a cell, and said foamed padding material comprising a gasified chemical foaming agent and a thermoplastic polyolefin elastomer.

2. The steering wheel of claim 1, wherein the thermoplastic polyolefin elastomer is weatherable and has a durometer shore A hardness of about 30 to about 90.

3. The steering wheel of claim 1, wherein the thermoplastic polyolefin elastomer includes a thermoplastic polyolefin polymer selected from the group consisting of polyethylene, polypropylene, polybutylene, polyisobutylene, polyoctene, copolymers of polyethylene, polypropylene, and polybutylene, and mixtures thereof.

44524-0800

4. The steering wheel of claim 3, wherein the thermoplastic polyolefin polymer is an elastomer or non-elastomer material.

5. The steering wheel of claim 3, wherein the thermoplastic polyolefin elastomer further includes another thermoplastic elastomer or rubber.

6. The steering wheel of claim 1, wherein the thermoplastic polyolefin elastomer comprises a mixture of ethylene-propylene copolymer, ethylene-propylene-diene terpolymer, and polypropylene.

7. The steering wheel of claim 1 wherein the foamed padding material is plasticizer-free.

8. The steering wheel of claim 1, said chemical foaming agent comprises an exothermic chemical foaming agent, an endothermic chemical foaming agent, or a mixture thereof.

9. The steering wheel of claim 1, wherein the chemical foaming agent prior to being gasified is in the

400280-455E660

form of a plurality of granules that are encapsulated with a resin carrier.

10. The steering wheel of claim 9, wherein the resin carrier is essentially the same material as the thermoplastic polyolefin elastomer.

11. The steering wheel of claim 1 wherein the foamed padding material further includes an additive selected from the group consisting of colorants, inorganic fillers, nucleating agents, and stabilizers.

12. A steering wheel comprising a rim portion, a spoke portion, and a plasticizer-free foamed padding material adhered to said rim portion and said spoke portion, said foamed padding material adhered to said rim portion having a first thickness and said foamed padding material adhered to said spoke portion having a second thickness different from said first thickness, said foamed padding material including a first portion and a second portion, said first portion having a cellular structure and a substantially uniform cell density, said second portion having a continuous external surface free of interruption by a cell, and said foamed padding material

FOOEE04E5E2E6E0

13. The steering wheel of claim 12, wherein the thermoplastic polyolefin elastomer is weatherable and has a durometer shore A hardness of about 30 to about 90.

15. The steering wheel of claim 12, wherein said chemical foaming agent comprises an exothermic chemical foaming agent, an endothermic chemical foaming agent, or a mixture thereof.

16. The steering wheel of claim 15, wherein the chemical foaming agent prior to being gasified is in the form of a plurality of granules that are encapsulated with a resin carrier.

17. The steering wheel of claim 16, wherein the resin carrier is essentially the same material as the thermoplastic polyolefin elastomer.

18. The steering wheel of claim 12 wherein the foamed padding material further includes an additive selected from the group consisting of colorants, inorganic fillers, nucleating agents, and stabilizers.

19. A method of manufacturing a foamed padding material for a steering wheel, said method comprising the steps of:

mixing a thermoplastic polyolefin elastomer and a chemical foaming agent;

foaming said thermoplastic polyolefin elastomer with said chemical foaming agent;

providing a steering wheel armature having a rim portion and a spoke portion; and

adhering said foamed thermoplastic polyolefin elastomer to said rim portion and said spoke portion of said steering wheel armature, said foamed thermoplastic polyolefin elastomer adhered to said rim portion and spoke portion of said steering wheel armature forming a foamed padding material including a first portion and a second

100230-4552660

20. The method of claim 19 wherein said foamed thermoplastic polyolefin elastomer is adhered to said rim portion and said spoke portion of said steering wheel armature by molding said foamed thermoplastic polyolefin elastomer to said rim portion and said spoke portion of said steering wheel armature.

22. The method of claim 19, wherein said thermoplastic polyolefin elastomer is weatherable and has a durometer shore A hardness of about 30 to about 90.

23. The method of claim 19, wherein the thermoplastic polyolefin elastomer comprises a mixture of

24. The method of claim 19, wherein said chemical foaming agent comprises an exothermic chemical foaming agent, an endothermic chemical foaming agent, or a mixture thereof.

26. The method of claim 25, wherein the resin carrier is essentially the same material as the thermoplastic polyolefin elastomer.

28. The method of claim 19, wherein said foamed padding material is plasticizer-free.

[illegible]

heating the mixture of said thermoplastic polyolefin elastomer and said foaming agent to a temperature above the melting temperature of said thermoplastic polyolefin elastomer;

providing a mold having a first mold wall and a second mold wall, said first wall portion defining a first cavity in which a rim portion of a steering wheel armature is disposed, said second wall portion defining a second cavity in which a spoke portion said steering wheel armature is disposed;

maintaining the temperature of the second wall portion at a second temperature, said second temperature being substantially lower than said first temperature;

[illegible]

foame
aid fi
ed the
below
lefin
astome
f said

31. The method of claim 30, wherein said foamed padding material adhered to said rim portion of said steering wheel armature has a first thickness and said foamed padding material adhered to said spoke portion has a second thickness different from said first thickness.

